

Presented By: BallastShop

Contact Phone: 18554841145

Customer Name:

Project Name:

Contact E-mail: support@ballastshop.com

Fixture Type:

GE
Lighting**66922 - LED 25 DC 24V PUS****GELD25DMV24PUS**

- ☞ Previous SKU: 901025024PUS
- ☞ 25W DC 24V constant voltage LED driver. Aluminum Casing. White color prevents shadowing in signage applications. Potted.
- ☞ Current: DC
- ☞ Designed for IP67.
- ☞ Reinforced insulation from input to output.
- ☞ High efficiency.
- ☞ PFC: > 0.98.
- ☞ Fully protected: Short circuit, Input voltage surge, Thermal, Secondary switch, Overload regulation, Over voltage protection. Self-resettable.AC/DC.
- ☞ Soft start.

GENERAL CHARACTERISTICS

Enclosure Type	Metal
Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	75 °C
Storage Temperature	-10 °C
Color	White
Primary Application	LED in- and outdoor lighting Street lighting Architectural lighting Sigge Indication and orientation lighting Ambiance lighting
Product Technology	LED
CV/CC	CV
CC/CVValue	24 V
Output Power (W)	25 W
Output Current (A)	1 A
Output Voltage[Nom]	24 V

PRODUCT INFORMATION

Product Code	66922
Description	GELD25DMV24PUS
Alternative Unit Of Measure	EACH
Standard Package Quantity	24
Ean UPC	043168669221
Standard Package GTIN	00043168669221
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
Sales Unit	Each
UCC	043168669221
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168669221
Standard Package GTIN	10043168669228
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168669221

ELECTRICAL CHARACTERISTICS

Output Current Frequency-Hertz	0 kHz
Supply Current Freq nominal Hz	60 Hz
Input Current Range[Max]	0.3 A
Input Current Range[Min]	0.1 A
Input Voltage Range[Min] (V)	120 V
Input Voltage Range[Max]	277 V