

**Presented By: BallastShop**

Contact Phone: 216-561-0069

Contact E-mail: support@ballastshop.com

Customer Name:

Project Name:

Fixture Type:



GE  
Lighting

66871 - null

**GELD18DMV350PU**

- Previous SKU: 901018350PU
- LED 18W DC 350mA - LED Driver, Constant Current, Aluminum Housing, Potted, with Leads
- Current: DC
- Dimmable with Trailing Edge dimmers
- Designed for IP67
- Reinforced insulation from input to output
- High efficiency
- PFC: > 0.95 Fully protected: Short circuit, Input voltage surge, Thermal, Secondary switch
- Overload regulation, Over voltage protection. Self-resettable
- AC/DC Soft start

**GENERAL CHARACTERISTICS**

Enclosure Type	Metal
Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	80 °C
Storage Temperature	-10 °C
Color	Black
Primary Application	LED in- and outdoor lighting Street lighting Architectural lighting Sigge Indication and orientation lighting Ambience lighting
Product Technology	LED
CV/CC	CC
CC/CVValue	350 mA
Output Power (W)	18 W
Output Current (A)	0.35 A
Output Voltage[Min]	4 V
Output Voltage[Max]	52 V

**PRODUCT INFORMATION**

Product Code	66871
Description	GELD18DMV350PU
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168668712
Standard Package GTIN	10043168668719
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168668712
Alternative Unit Of Measure	EACH
Standard Package Quantity	24
Ean UPC	043168668712
Standard Package GTIN	00043168668712
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
Sales Unit	Each
UCC	043168668712

**ELECTRICAL CHARACTERISTICS**

Output Current Frequency-Hertz	0 kHz
Supply Current Freq nominal Hz	50 Hz
60 Hz	Input Current Range[Max]
0.17 A	Input Current Range[Min]
0.09 A	Input Voltage Range[Min] (V)
120 V	Input Voltage Range[Max]