



T8 U-BENT LED LIGHT TUBE

by Hyperikon®



Base
G13



Voltage
120-277V



Instant On
(No Delay)



Lifespan
45,000+ Hrs



5 Years
Warranty



CRI
85+



Beam Angle
160°



UV free
Mercury free



Damp location
suitable

- Replaces any T5 fluorescent tube
- Enhanced driver design
- High Efficacy, meaning more lumens per watt
- 45,000+ hours of lifespan, more than 26 years based on 5Hrs/day average
- Device complies with Part 15 of the FCC Rules
- Device has been tested and found to comply with the limits for a class B digital device



SPECIFICATIONS

Hyperikon Code	Type	Wattage	Voltage	Kelvin	CRI	Length	Base	Beam Angle	Lumens	Efficacy
8U1000701	Clear	18W	120-277V	4000K	85+	2ft	G13	160°	2050Lm	114Lm/W
8U1000702	Clear	18W	120-277V	5000K	85+	2ft	G13	160°	2100Lm	117Lm/W
8U2000701	Frosted	18W	120-277V	4000K	85+	2ft	G13	160°	2000Lm	111Lm/W
8U2000702	Frosted	18W	120-277V	5000K	85+	2ft	G13	160°	2050Lm	114Lm/W



MODEL DESIGN



WARNINGS AND CAUTIONS

- Turn power off before inspection, installation or removal. Risk of electric shock - do not use where directly exposed to water or weather.
- Suitable for damp locations outside as well as inside.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.

