

## Constant Voltage LED Driver


# **Model Number AC-60VD24AER**

Input Voltage: 120-277V Input Frequency: 50/60Hz Side Mount/Leads

### **ELECTRICAL SPECIFICATIONS:**

Output Power		Min PF (full load)	Max THD (full load)				Minimum Starting Temp	Efficiency Up To	IP Rating	Dimming Range	Dimming Protocol
60W	0.6A @ I20V 0.26A @ 277V	>0.95	<10%	24V ±5%	0.25 to 2.5A	90° C	-40° C	86.6%	IP66	10-100%	0-10V

#### **WIRING:**



Lead Lengths							
Black	Black 5.9" Blue		5.9"	Purple	5.9"		
White	5.9"	Red	5.9"	Gray	5.9"		

#### **PHYSICAL:**



Dimensions				
Length	12.8"			
Width	1.34"			
Height	1.14"			
Mounting Length	12.5"			
Weight	xx lbs.			
Case Qty.	xx pcs.			

#### **SAFETY:**

- UL and cUL Recognized
- UL1310 Class 2
- UL Outdoor Type I
- Class A sound rating
- Overload Protection
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50.000 hours at Tcase of ≤75°C
- LED driver has a life expectancy of 100,000 hours at Tcase of ≤65°C
- Warranty: 5 yrs based on max case temp of <75°C; 3 yrs based on max case temp of 90°C\*
- Input/Output Isolation
- FCC Title 47 CFR Part 15
- Surge Protection (2 KV)

## **INSTALLATION:**

- LED drivers shall be installed inside electrical enclosures
- 18 AWG 600V/105C tinned strand copper lead-wires are required for installation
- Max Remote installation distance is 18 ft
- LED driver cases should be grounded



\*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years when operated at max case temp of up to <75°C; 3 years from date of manufacture when operated at a max case temp of up to 90°C when properly installed and under normal conditions of use. See <u>aceleds.com</u> for complete warranty policy.



3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com

ROHS COMPLIANT LEAD-FREE

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.