


LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



4000 Series Adapter



- Sealed, Water Resistant Ballast
- Center Mount Design
Ratcheted Screw Shell
- Two Piece Unit, Not A Throw-Away
- Saves Energy - Uses 75% Less Energy Than Incandescent Equivalent
- Long Life - Lasts 10 Times Longer Than Incandescent Equivalent, Fewer Lamp Changes
- 45,000+ Hour Class P Thermally Protected **Magnetic** Ballast/10,000 + Hour Replaceable Lamp Life
- **Instant-Start Twin Tube (LI) 13 Watt Lamp Upon Request**
- Available With Quad Lamp (Q) or Single Twin Tube
- Durable LEXAN Housing
- 120 Volt/60 Hz

Model	Watts	Equivalent Incandescent	Initial Lumens	Rated Average Lamp/Ballast Life	Dimensions			Min. Start Temp
					W 1	W 2	H	
4000-L	5	25 watts	250	10,000+/45,000+ Hrs.	1-15/16"	1-15/16"	6-3/4"	20 ° F
4200-L	7	40 watts	400	10,000+/45,000+ Hrs.	1-15/16"	1-15/16"	8"	20 ° F
4500-L	9	50 watts	600	10,000+/45,000+ Hrs.	1-15/16"	1-15/16"	9-1/4"	20 ° F
4600-L	9 Quad	50 watts	600	10,000+/45,000+ Hrs.	1-15/16"	1-15/16"	7-1/8"	20 ° F
4700-L	13	60 watts	900	10,000+/45,000+ Hrs.	2-1/8"	2-1/8"	9-15/16"	20 ° F
4800-LQ	13 Quad	60 watts	900	10,000+/45,000+ Hrs.	2-1/8"	2-1/8"	7-7/16"	20 ° F
Cool White (CW) Lamps Available Upon Request								

**Vertically Integrated Manufacturer
Made In USA**