

S50MLTLC3M




50W S68

High Pressure Sodium

60Hz HX-HPF

Specification Sheet

Input Volts	120	208	240	277	
Regulation					
Line Volts	±5%	±5%	±5%	±5%	
Lamp Watts	±10%	±10%	±10%	±10%	
Power Factor (min)	90%	90%	90%	90%	
Input Watts	66 W	66 W	66 W	66 W	
NOM. Open Circuit Voltage	120 V	120 V	120 V	120 V	
Line Current (Amps)					
Operating	0.55	0.35	0.30	0.25	
Open Circuit	1.05	0.60	0.55	0.45	
Starting	0.60	0.35	0.30	0.25	
Recommended Fuse (Amps)	3	2	2	2	
Lamp Dropout Voltage (Line)	95 V	165 V	190 V	220 V	
UL Temperature Ratings					
Insulation Class	H (180°C)	H (180°C)	H (180°C)	H (180°C)	
Temperature Code	A	A	A	A	
MIN. Starting Temperature	-40°F -40°C	-40°F -40°C	-40°F -40°C	-40°F -40°C	
CAPACITOR Specifications					
Microfarads	5 uf	5 uf	5 uf	5 uf	
Volts (min.)	280 V	280 V	280 V	280 V	
60Hz Test Procedures					
High Potential Test 1 Minute	2000 V	2000 V	2000 V	2000 V	
High Potential Test 1 Second	2500 V	2500 V	2500 V	2500 V	
Secondary Open Ckt Voltage (V)	110 - 140	110 - 140	110 - 140	110 - 140	
Secondary Current Shorted (A)	1.35 - 1.70	1.35 - 1.70	1.35 - 1.70	1.35 - 1.70	
Input Operating Current (A)	0.50 - .065	0.25 - 0.40	0.25 - 0.35	0.20 - 0.30	
Input Open Circuit Current (A)	0.50 - 1.55	0.30 - 0.90	0.25 - 0.80	0.20 - 0.70	
Input Short Circuit Current (A)	0.35 - 0.70	0.20 - 0.40	0.15 - 0.35	0.15 - 0.30	
Core and Coil Specifications					
Dimension A	1.38 in	1.38 in	1.38 in	1.38 in	
Dimension B	2.68 in	2.68 in	2.68 in	2.68 in	
Weight	4.10 lbs	4.10 lbs	4.10 lbs	4.10 lbs	
Lead Lengths (inches)	12-14	12-14	12-14	12-14	
Coil Material (Pri. / Sec.):	Cu / Cu	Cu / Cu	Cu / Cu	Cu / Cu	



Document #: 010-9668-06
Date: 11/17/2008
Status: Production
Replaces Catalog #: 12310-95

Data is based upon tests performed by Universal Lighting Technologies in a controlled environment and is representative of relative performance. Actual performance may vary depending on operating conditions. Specifications are subject to change without notice.

Universal Lighting Technologies

26 Century Blvd. Suite 500 - Nashville, TN 37214

Phone 1-800-225-5278 Fax 1-800-206-0035

www.unvlt.com

11/17/2008